

OSM iMX93 PRODUCT BRIEF



Toradex AG | Ebenaustrasse 10 | 6048 Horw | Switzerland | T: +41 41 500 48 00 | info@toradex.com
www.toradex.com | www.torizon.io | developer.toradex.com | community.toradex.com

All information provided is for information purposes only and no guarantees are expressed or implied. No responsibility for any errors, omissions or hyperlinked content is assumed. Names and logos in this document may be trademarks of their respective companies. © Copyright 2025, Toradex AG.




OSM iMX93 Product Brief

Toradex OSM - Compact, Solderable, High-Volume ready SoMs

The OSM Size-S form factor delivers a compact 30×30 mm footprint with a fully solderable, connector-less BGA interface. Designed to be completely machine-processable during soldering, assembly, and testing, OSM enables space-efficient designs, ideal for cost-optimized and high-volume products.

If your application demands miniaturization, long-term reliability, and a solderable SoM, OSM modules are a strong fit, enhanced by Toradex's high quality, industrial reliability, and comprehensive documentation and support.




Is Solderable For You?

Selecting a solderable SoM is not only about product requirements, it also depends on your production capabilities. OSM modules are best suited for manufacturing lines equipped with automated SMT (Surface-Mount Technology) and reflow processes. If your factory supports these workflows, OSM provides an efficient, scalable integration path.

If your production process relies on manual assembly, requires easier handling during development, or benefits from a pluggable module for prototyping or field replacement, the Lino family is a better fit. It offers similar compactness through 2x100-pin board-to-board connectors with stacking heights down to 1.5 mm.

| Features / Form Factor | Toradex OSM Modules | Toradex Lino Modules |
|------------------------------|-------------------------------|----------------------|
| Form Factor | Solderable, OSM Size-S | Board-to-board, Lino |
| Manufacturing Process | SMT and reflow processes | Manual assembly |
| SoM Physical Size | 30x30mm, Ultra-compact design | |
| Production Volume | High volume projects | |

Toradex OSM Family



Solderable interface:
Eliminates connectors, enabling fully automated production.

Leverage Your Own Automated Line:
Uses existing soldering and inspection equipment for seamless integration.

Treat Soldering Like a Component:
Mounts directly to your PCB using standard SMT and reflow processes.

Compact Design Fit:
Enables ultra-small enclosures and sleek product layouts.

Perfect for High-Volume Projects:
Fully machine-processable for scalable and repeatable production.

Seamless software integration:
Powered by Torzino OS and Torzino Cloud.

Toradex Lino Family



Board-to-board connector:
Simplifies integration, enables easy module upgrades and serviceability.

Simpler manufacturing infrastructure:
Less demanding process control and complexity, reducing production costs.

Flexible Prototyping:
Swap modules during development to test performance or configurations quickly.

OSM iMX93 Product Brief

OSM Family SoMs


The **OSM family** delivers efficient, secure, and modern processing in a rugged, **solderable form factor** designed for **space-constrained devices** and **high volume applications**. Built on NXP's i.MX 9 processors, it provides a stable and scalable platform for long-life designs that demand compact size and reliable performance, optimized for machine-assembled production lines.

With multiple modules sharing the same industry-standard OSM footprint and software ecosystem, the family offers effortless scalability, from streamlined control solutions to AI-enabled connected devices, without relying on bulky connectors or custom mechanical designs.

| Features / SoMs | OSM iMX91 | OSM iMX93 |
|---------------------------|---|--|
| Form Factor | Solderable, OSM Size-S | |
| SoM Physical Size | 30x30mm | |
| Number of pins | 332 BGA pins | |
| CPU | 1x Arm Cortex-A55 (up to 1.4 GHz) | Up to 2x Arm Cortex-A55 (up to 1.7 GHz) |
| MCU | - | 1x Cortex-M33 (250 MHz) |
| RAM Technology | LPDDR4 (up to 2.4 GT/s) | LPDDR4 (up to 3.7 GT/s) |
| Storage Technology | On-module eMMC | |
| Connectivity | Dual Ethernet (with TSN), 2x CAN FD, USB 2.0 (OTG + Host), I ² C, I ² C, SPI, UART, PWM, GPIO, ADC, SDIO/SD/MMC, I ² S | |
| NPU | - | 0.5 TOPS |
| Multimedia | Headless design for compact controllers and gateways | MIPI DSI display, LVDS, MIPI CSI-2 camera and 2D graphics acceleration |
| Typical use cases | Industrial controllers, PLCs, IoT gateways, smart sensors | HMI, smart vision nodes, AI-enabled controllers, connected IPCs |

Each **OSM SoM** is positioned to offer a straightforward and seamless scalability path. The **OSM iMX91** provides an efficient, reliable entry point for control-focused designs, while the **OSM iMX93** adds multimedia processing and edge AI acceleration for more feature-rich devices.

Unified by the same **compact, solderable OSM form factor** and software ecosystem, they deliver a consistent, connector-less platform that simplifies scaling product lines and ensures long-term design continuity.



OSM iMX93 Product Brief


Interfaces Overview

The **OSM iMX93 System on Module (SoM)** combines scalable performance, advanced connectivity, and industrial reliability in a compact, solderable form factor. Based on the **NXP i.MX 93** applications processor, it integrates dual Arm® Cortex®-A55 cores, an Arm® Cortex®-M33 real-time core, and an optional Neural Processing Unit (NPU), enabling efficient edge AI acceleration and responsive system control.

Designed for **HMDIs, vision-based systems, and intelligent gateways**, the OSM iMX93 streamlines development with its **solderable, connector-less design**, on-module LPDDR4 memory, eMMC storage, and a versatile set of multimedia and industrial interfaces, fully supported by Toradex's long-term software ecosystem.



Open Standard Module™
(OSM)



Ultra-Compact and
Solderable



Multimedia Support
for HMI



AI at the Edge for IoT
Applications




Industrial Reliability

The table below summarizes the main interfaces and configuration options of the OSM iMX93.

| Features | Total (up to) |
|--|---------------|
| | |
| | |
| Analog | |
| Analog Input (ADC) | 2 |
| | |
| Audio | |
| I2S | 1 |
| | |
| Camera | |
| MIPI CSI-2 | 1 |
| | |
| Display | |
| MIPI DSI | 1 |
| | |
| LVDS (dual channel) | 1 |
| | |
| Low speed | |
| I2C | 2 |
| SPI | 2 |
| UART Console | 1 |
| UART (Rx/Tx only, 2x with RTS/CTS) | 4 |
| PWM | 3 |
| CAN FD | 2 |
| GPIO | 24 |
| JTAG | 1 |
| | |
| Network | |
| RGMII (Gigabit Ethernet) | 2 |
| | |
| Storage | |
| SD/SDIO/MMC | 2 |
| | |
| USB | |
| USB 2.0 (Host/OTG, 1x Serial downloader) | 2 |

OSM iMX93 Product Brief

Block Diagram



Legend



OSM iMX93 Product Brief

Configuration Overview

The OSM iMX93 SoM delivers scalable performance for industrial and IoT applications that require advanced multimedia and edge AI capabilities. Its solderable, connector-less form factor enables robust, compact integration within a 30x30mm PCB footprint, ideal for space-constrained designs. With multiple configuration options for memory and storage, developers can tailor the module to their specific system requirements.

The first configuration to be released is shown in the table below: OSM iMX93 Dual 2GB IT.

| Family | iMX93 Segment | A-Core Qty | RAM | eMCC | Temp. Sensor | TPM | Temperature |
|-----------|---------------|------------|-----|------|--------------|-----|-------------|
| OSM-IMX93 | 5 | 2 | -2G | -16G | -T | -N | -IT |

Additional configurations will be developed over time. In the meanwhile, the tables below summarize the available configuration elements and how they can be combined. Use the "Configuration Inputs" tables to fill in the open fields from "NPI part number table" in order to build the desired configuration.

For additional specific requirements or tailored options, please, get in touch with us.

Note: The New Product Introduction (NPI) part number nomenclature shown below does not reflect volume or sellable part numbers from Toradex. They should only be used to communicate your desired configuration.

NPI part number table

| Family | iMX93 Segment | A-Core Qty | RAM | eMCC | Temp. Sensor | TPM | Temperature |
|-----------|---------------|------------|-----|------|--------------|-----|-------------|
| OSM-IMX93 | | | | | | | |

Configuration Inputs

| iMX93 Segment | Description | A-Cores Qty | Max Frequency | DRR Speed | NPU |
|---------------|------------------------|-------------|---------------|------------|-----|
| 5 | Full Featured with NPU | 1/2 | 1.7 GHz | 3.7 GT/s | Yes |
| 3 | Without NPU | 1/2 | 1.7 GHz | 3.7 GT/s | |
| 0 | Reduced | 1/2 | 900 MHz | 1.866 GT/s | |

| RAM Density | |
|-------------|--------|
| -256M | 256 MB |
| -512M | 512 MB |
| -1G | 1 GB |
| -2G | 2 GB |

| eMMC Capacity | |
|---------------|--------|
| -4G | 4 GB |
| -8G | 8 GB |
| -16G | 16 GB |
| -32G | 32 GB |
| -64G | 64 GB |
| -128G | 128 GB |
| -256G | 256 GB |

| Temperature Sensor | |
|--------------------|---------------|
| -T | Assembled |
| -N | Not assembled |

| TPM | |
|-----|-----------------------|
| -T | TPM 2.0 assembled |
| -N | TPM 2.0 not assembled |

| Temperature | |
|-------------|----------------------------|
| -IT | Industrial (-40°C to 85°C) |
| -ET | Extended (-25°C to 85°C) |
| -CT | Commercial (0°C to 70°C) |

Contact us for more information, or visit our website product page: [OSM iMX93 product page](#).



OSM iMX93 Product Brief



Easily Develop, Manage and Secure Your Linux Devices

Torizon is a ready-to-use Linux-based ecosystem that simplifies the development, management, and security of embedded devices. Built on a robust Linux foundation, it accelerates time-to-market with a production-grade software stack and no vendor lock-in.

Designed for reliability at scale, Torizon offers secure over-the-air updates, real-time capabilities, and streamlined device management throughout the product lifecycle. It empowers you to build, deploy, and maintain Linux devices with confidence.



To explore the full potential of the Torizon ecosystem, visit Torizon.io

 **Toradex**
Swiss. Embedded. Computing.

Toradex AG | Ebenaustrasse 10 | 6048 Horw | Switzerland | T: +41 41 500 48 00 | info@toradex.com
www.toradex.com | www.torizon.io | developer.toradex.com | community.toradex.com

All information provided is for information purposes only and no guarantees are expressed or implied. No responsibility for any errors, omissions or hyperlinked content is assumed. Names and logos in this document may be trademarks of their respective companies. © Copyright 2025, Toradex AG.

