




IMB-1220



IMB-1222

10th GEN INTEL® CORE™ PROCESSORS FULL RANGE OF INDUSTRIAL MOTHERBOARDS

The 10th Gen is coming




CML-S / Xeon Processors

- ⦿ Up to 10 Cores
- ⦿ Up to DDR4-2933
- ⦿ Increased multi-threaded performance

	9 th Gen Coffee Lake	10 th Gen Comet Lake	Advantage of CML-S
LGA	Socket 1151	Socket 1200	Improve power delivery
CPU	Up to 8 Cores	Up to 10 Cores	Performance enhance
Multi-Thread	Only Core i9 support	Core i9/i7/i5/i3/Pentium/Xeon support	
DRAM	Up to DDR4-2666	Up to DDR4-2933	




Spec / Benchmark	Coffee Lake Core i7 i7-9700	Comet Lake Core i5 i5-10500 	Performance Increase (%)
Official CPU Price (USD)	\$323 ~ \$335	\$192 ~ \$202	Saving \$13X
Base Frequency	3.0 GHz	3.1 GHz	
Max Turbo Frequency	4.7 GHz	4.5 GHz	
CPU Cores / Threads	8 / 8	6 / 12	
Cinebench R15 CPU Score	1,221	1,355	11% ▲
3DMark Sky Diver Physics	14,040	16,006	14% ▲
3DMark Fire Strike Physics	15,125	17,421	15.2% ▲

◆ Advantage of CML-S CPU

Performance: **CML i5** is better than **CFL i7** CPU (Up to 15%)

Cost: **Saving \$130** at least



Spec / Benchmark	Coffee Lake Core i3 i3-9100	Comet Lake Core i3 i3-10100 	Performance Increase (%)
Official CPU Price (USD)	\$122	\$122	
Base Frequency	3.6 GHz	3.6 GHz	
Max Turbo Frequency	4.2 GHz	4.3 GHz	
CPU Cores / Threads	4 / 4	4 / 8	
Sandra CPU GOPs Score	100	139.48	39.5% ▲
Cinebench R15 CPU Score	643	881	37% ▲
3DMark Sky Diver Physics	8,264	11,352	37.4% ▲
3DMark Fire Strike Physics	8,720	12,436	42.6% ▲

◆ Choosing CML-S CPU, the performance can increase **40%**

400 Series M/B Product Lineup




	Mini-ITX (High-Rise I/O)	Mini-ITX (Thin I/O)	Micro ATX	ATX
W480E	IMB-X1220-L	IMB-X1222-WV	IMB-X1313	IMB-X1711
Q470E	IMB-1220-D	IMB-1222	IMB-1313	IMB-1711
	IMB-1220-L	IMB-1222-WV		
H420E	IMB-1221-D	IMB-1223		
	IMB-1221-L	IMB-1223-WV		



CML



CFL



IMB-1220-D + i5-10500

VS

IMB-1211-D + i7-9700




Cost Saving **\$1XX**

Win10 License Saving [**High-end Value**]





Performance increase **15%**

Spec Comparison – IMB-1211 / IMB-1220




	IMB-1211-D (Q370)	IMB-1220-D (Q470E)
Aircraft tail PCI-E slot	No	Yes
MOSFET Heatsink	No	Yes
Replaceable DC-in Fuse	No	Yes
CMOS Battery Charge	No	Yes
M.2 Key B with SIM	No	Yes
HDMI2.0a	No	Yes
Intel 2.5G LAN	No	Yes
USB 3.2 Gen1 Header	No	Yes (2 Ports)
ATX/DC_IN Co-design	No	BOM Option

Spec Comparison – IMB-1213 / IMB-1222-WV



	IMB-1213 (Q370)	IMB-1222-WV (Q470E)
Wide Range DC-in	12V/19~28V	12~28V
Thunderbolt Header	No	Yes
MOSFET Heatsink	No	Yes
Aircraft tail PCI-E slot	No	Yes
M.2 Key B with SIM	No	Yes
HDMI2.0a	No	Yes
Intel 2.5G LAN	No	Yes
USB 3.2 Gen1 Header	No	Yes (2 Ports)

Key Feature for Mino



SPEEDY

Intel® 2.5G LAN

- Intel i225 LAN adopt
- Boost networking performance up to **2.5X**
- Faster file transfers, smoother high quality video streaming




STABILITY

MOSFET Heatsink

- Dissipate heat efficiently
- Bring down MOSFET temperature
- Enhance the utilized efficiency of MOSFET
- Suitable for Fanless system

*Only for Mini-ITX models




SERVICEABILITY

Replaceable Fuse

- Design 20A Fuse for Input Power protection
- Enhance serviceability


*Only for Mini-ITX models



PERFORMANCE

HDMI 2.0a

- 4096x2160@60Hz
- High Dynamic Range (HDR) support
- Fully enjoy Premium 4K UHD content



DURABILITY

CMOS Battery Charge

- Design PWR_BAT1 header for Long-Life RTC battery application
- Choose **chargeable battery** by customer to support this function

*IMB-1222/IMB-1223/IMB-X1222 Series M/B don't support it






SECURITY

Onboard TPM2.0

- Integrated Infineon TPM2.0 SLB9670
- Provide hardware-based security for Industrial data protection

*Q470E/W480E M/B Support



DIVERSITY

Multi-M.2 Slots

- Key M 2280 with PCIe4
- Key E 2230
PCIe/USB2.0/CNVi for WiFi/BT
- Key B 3042/3052
PCIe/USB3.0/USB2.0 and
SIM socket for 4G/5G

*Key M: PCIe4 for Q470E/W480E, PCIe2 for H420E
Key B: Only 3042 for IMB-1220/1221



FLEXIBILITY

Wide Range DC-in

- 12~28V DC-in design
- Flexible acceptance of inconsistent power input
- OVP/UVP for Protection

*Only IMB-X1222-WV/IMB-1222-WV/IMB-1223-WV support 12~28V



EXPANSIBILITY

PCI-E Riser Card


- PCIe x16 slot support
- PCIe x16 to x8/x8 or x8/x4/x4 Riser Card
- Without PCIe Clock buffer to support extension slots

*IMB-1711 and IMB-X1711 don't support it


IMB-1313 & IMB-1711 Feature



Power Design	Dr. MOS with Digital PWM Support CPU up to 125W
DIMM Bracket	Design Retention bracket for Memory Modules
USB Ports	Rear: 4*USB3.2 Gen2 + 2*USB2.0 Internal: 4*USB3.2 Gen1 (2*Header) + 2*USB2.0
SATA Ports	IMB-1313: 8*SATA3 IMB-1711: 6*SATA3 1*M.2 Key M (Shared with SATA3_5/6)
Other	MCU Mini58 Support HDMI2.0a/Intel 2.5G LAN/ TPM Onboard CMOS Battery Charge (PWR_BAT1) M.2 Key B with SIM socket for 5G M.2 Key M with SATA/PCIe x4 M.2 Key E with PCIe x1/USB2.0/CNVi * PCIe1 Riser card support for IMB-1313 * 2x PCI Slot for IMB-1711



IMB-1313





IMB-1711



Dr. MOS

With **efficiency up to 95%**, Dr. MOS is more efficient during normal operation.

Dr. MOS is able to give **less power losses** to maintain lower temperature under heavy Loading, thus providing improved thermal result and **superior performance**




Dr. MOS

Driver IC

Low Side MOSFET

High Side MOSFET





Traditional Design



DIMM Bracket

Design **Retention bracket** for Memory Modules.

Memory operation will be under stronger fixture and **reduce Vibration/Shock** from external environment, thus providing **durability** and **stability** for Industrial application.



*DIMM Bracket is optional



- Full Product-line for W480E Chipset
- Support Xeon W-1200 Series CPU and ECC memory



CPU	TDP	Core/Threads	ECC Support
W-1290E/W-1290TE	95W/35W	10/20	Yes
W-1270E/W-1270TE	80W/35W	8/16	Yes
W-1250E/W-1250TE	80W/35W	6/12	Yes
i3-10100E/i3-10100TE	65W/35W	4/8	Yes


*About the detailed CPU support for each M/B, please refer to the CPU support list



IMB-X1220-L



IMB-X1222-WV



IMB-X1313



IMB-X1711



	Mini-ITX (High-Rise I/O)	Mini-ITX (Thin I/O)	Micro ATX	ATX
Haswell (Q87)*	IMB-181	IMB-184	IMB-380	IMB-780 IMB-781
Skylake/Kabylake (Q170)	IMB-194	IMB-190	IMB-390	IMB-790
Coffee Lake (Q370)	IMB-1211	IMB-1213 IMB-1215	IMB-1311 IMB-1312	IMB-1710
Comet Lake (Q470E)	IMB-1220-D IMB-1220-L	IMB-1222 IMB-1222-WV	IMB-1313	IMB-1711


***Q87 Chipset will EOL in 2021**



	Mini-ITX (High-Rise I/O)	Mini-ITX (Thin I/O)	Micro ATX	ATX
Haswell (H81)*	IMB-185	IMB-183	IMB-385	IMB-785
Skylake/Kabylake (H110)	IMB-195	IMB-191 IMB-192 IMB-193	IMB-391	IMB-791 IMB-792
Coffee Lake (H310)	IMB-1210	IMB-1212 IMB-1214	IMB-1310	
Comet Lake (H420E)	IMB-1221-D IMB-1221-L	IMB-1223 IMB-1223-WV		

***H81 Chipset will EOL in 2021**


Summary



Comet Lake
i5-10500

Coffee Lake
i7-9700


CPU Price



Comet Lake
i5-10500

Coffee Lake
i7-9700

Performance





Information and content in this document is provided in connection with ASRock Industrial® products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

Except as provided in ASRock Industrial's terms and conditions of sale for such products, ASRock Industrial assumes no liability whatsoever, and ASRock Industrial disclaims any express or implied warranty, relating to sale and/or use of ASRock Industrial® products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right.

ASRock Industrial may make changes to specifications and product descriptions at any time, without notice.

All product and figures specified are preliminary based on current expectations, and are subject to change without notice.

No product or component can be absolutely secure.

Performance tests, such as Cinebench and 3DMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary.

*Other names and brands may be claimed as the property of others.

Copyright © 2020 ASRock Industrial Corp. All Rights Reserved



Thank you!

